

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all previous versions, and listings, of claims in this application.

**Listing of Claims:**

1. (Currently Amended) A dishwasher comprising:  
  
a control panel;  
  
a front panel disposed at a front of the control panel;  
  
a front display unit slidably coupled to at least one of the control panel and the front panel and including a display portion for displaying operational status of the dishwasher; and  
  
a sliding latch and a latch mounting slot for slidably coupling the front display unit,  
  
wherein the front display unit is disposed between the control panel and the front panel,  
and detachably coupled to at least one of the control panel and the front panel.
2. (Original) The dishwasher according to claim 1, wherein the sliding latch and the latch mounting slot are formed in at least one pair or more.
3. (Original) The dishwasher according to claim 2, wherein the sliding latch and the latch mounting slot are respectively formed opposite to one another.
4. (Original) The dishwasher according to claim 1, wherein the sliding latch is formed on the front display unit.

5. (Previously Presented) The dishwasher according to claim 4, wherein the latch mounting slot is formed on at least one of the control panel and the front panel.

6. (Original) The dishwasher according to claim 1, wherein the sliding latch includes an extended portion extending a predetermined distance and a bent portion bending from the extended portion.

7. The dishwasher according to claim 1, wherein the latch mounting slot includes an inserting slot having a predetermined width and a securing slot having another predetermined width less than the width of the inserting slot.

8. (Canceled)

9. (Original) The dishwasher according to claim 1, further comprising a positioning tab and a tab receptacle for positioning the front display unit after the front display unit has completed sliding.

10. (Original) The dishwasher according to claim 9, wherein the positioning tab is formed on the front display unit, and the tab receptacle is formed on at least one of the control panel and the front panel.

11. (Original) The dishwasher according to claim 9, wherein the positioning tab and the tab receptacle are positioned to couple when the front display unit has completed sliding.

12. (Original) The dishwasher according to claim 1, wherein the front panel includes a display window formed thereon for allowing information displayed by the front display unit to be viewed from the outside.

13. - 15. (Canceled)

16. (Currently Amended) A manufacturing method of a dishwasher, comprising:  
preparing a control panel, a front panel, and a front display unit;  
forming a sliding latch and a latch mounting slot for sliding the front display unit;  
disposing the front display unit between the control panel and the front panel; and  
coupling the front display unit to at least one of the control panel and the front panel by sliding the sliding latch in the latch mounting receptacle,  
wherein the front display unit is detachably coupled to at least one of the control panel and the front panel.

17 (Original) The manufacturing method according to claim 16, wherein the forming of the sliding latch includes forming an extended portion and a bent portion bent from the extended portion, and the forming of the latch mounting slot includes forming an inserting slot having a predetermined width and a securing slot having another predetermined width less than the width of the inserting slot.

18. (Original) The manufacturing method according to claim 17, wherein the coupling of the front display unit includes:

inserting the sliding latch in the latch mounting slot; and

sliding the sliding latch for securing the sliding latch in the securing slot.

19. (Original) The manufacturing method according to claim 16, wherein the preparing of the control panel, the front panel, and the front display unit includes forming a positioning tab and a tab receptacle.

20. (Original) The manufacturing method according to claim 19, wherein the coupling of the front display unit includes positioning the front display unit by coupling the positioning tab to the tab receptacle.